



Mobil Delvac™ Super 1300 C (美孚黑霸王™)

Mobil Commercial Vehicle Lube, China

High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ Super 1300 C products are high performance diesel engine oils that provide proven engine protection of diesel engines operating in on and off-highway severe service applications. Mobil Delvac Super 1300 C products are recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

The technology in Mobil Delvac Super 1300 C products delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Clean engines and long engine life

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from Chinese, European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

Mobil Delvac Super 1300 C meets or exceeds the requirements of the following industry specifications:	10W-30	15W-40	20W-50
API CH-4	X	X	X
API SJ Engine Test Requirements	X	-	-
Cummins CES 20076	-	X	-

Mobil Delvac Super 1300 C has the following builder approvals:			
MB-Approval 228.3	-	X	X
MAN M 3275-1	-	X	X

Mobil Delvac Super 1300 C is also recommended by ExxonMobil for use in applications requiring:			
API CG-4/CF-4/CF/SJ	-	X	X

Mobil Delvac Super 1300 C is also recommended by ExxonMobil for use in applications requiring:			
API CG-4/CF-4/CF	X	-	-
ACEA E2	-	X	X
Volvo VDS-2	X	X	-
Volvo VDS	-	-	X

Typical Properties

SAE Grade	10W-30	15W-40	20W-50
Viscosity, ASTM D 445			
cSt @ 40°C	70	107	150
cSt @ 100°C	10.7	14.7	17.5
Viscosity Index, ASTM D 2270	138	135	128
Sulfated Ash, wt%, ASTM D 874	1.2	1.1	1.1
Total Base # , mg KOH/g, ASTM D 2896	9.9	9.9	10.4
Pour Point, °C, ASTM D 97	-27	-27	-30
Flash Point, °C, ASTM D 92	220	244	239
Density @ 15°C kg/l, ASTM D 4052	0.88	0.88	0.89

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil™ logotype, the Pegasus design, Mobil Delvac™ (and any other trademarks) are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

10-2016

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved.